



TITAN

PORCELAIN TILES & CERAMIC MOSAICS



TITAN


PORCELAIN TILES & CERAMIC MOSAICS

Titan Bone



39x78 cm | 15"x30"
AC (SATIN) - DCOF WET ≥0.42
PORCELAIN TILE

Titan White



39x78 cm | 15"x30"
AC (SATIN) - DCOF WET ≥0.42
PORCELAIN TILE

Titan Gray



39x78 cm | 15"x30"
AC (SATIN) - DCOF WET ≥0.42
PORCELAIN TILE

Titan Charcoal



39x78 cm | 15"x30"
AC (SATIN) - DCOF WET ≥0.42
PORCELAIN TILE

**Titan Bone
Herringbone Mosaic**




1"x3" PRESSED
AC (SATIN) - DCOF WET ≥0.42
CERAMIC FLOOR/WALL TILE

**Titan White
Herringbone Mosaic**




1"x3" PRESSED
AC (SATIN) - DCOF WET ≥0.42
CERAMIC FLOOR/WALL TILE

**Titan Gray
Herringbone Mosaic**



1"x3" PRESSED
AC (SATIN) - DCOF WET ≥0.42
CERAMIC FLOOR/WALL TILE

**Titan Charcoal
Herringbone Mosaic**





1"x3" PRESSED
AC (SATIN) - DCOF WET ≥0.42
CERAMIC FLOOR/WALL TILE



TITAN

PORCELAIN TILES & CERAMIC MOSAICS

PRODUCT INFORMATION

	Product	Finish	Edge	Work Size	Thick	Faces	Sq. Ft./ Carton	Pieces/ Carton
	Wall/Floor 15"x30"	Satin	Pressed	391.5x776.0 mm 15 3/8" x 30 1/2"	8.0 mm	16	16.35	5
	Wall/Floor 1x3 Herringbone Dot-mounted Mosaic	Satin	Pressed	sheet size 22.86 x 30.48 cm 9"x12"	6.0 mm	10	6.00	10

USAGE RECOMMENDATION

	Target DCOF wet	Porcelain Suitable	Ceramic/Mosaic Suitable
Dry & Level – Interior Floor (Residential / Light Commercial)	N/A	✓	✓
Wet & Level – Interior Floor (Residential / Light Commercial)	≥ 0.42	✓	✓
Shower Floors (Residential / Light Commercial)	≥ 0.42	✓	✓
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60		
Ramps & Inclines	≥ 0.65		
Exterior Walls Applications	N/A	✓	
Interior Walls/Backsplashes	N/A	✓	✓
Interior Countertops	N/A	✓	✓
Facades	N/A	✓	
Pool Linings	N/A		

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

Note: Porcelain tiles are suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

INSTALLATION AND CARE

Grout Joint Recommendation 1/8"

Shade Variation V3 - MODERATE VARIATION

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane's recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Eliane recommends using a cloth with water and a neutral cleaner (soap less) or a general household cleaner.

PERFORMANCE CHARACTERISTICS

	ASTM#	Porcelain Result	Ceramic Result
Water Absorption	C373	≤ 0.5%	≤ 3%
Breaking Strength	C648	≥ 275 lbs	> 250 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	≥0.42	≥0.42
Frost Resistance	C1026	Yes	No
Scratch Hardness	MOHS	7 - 8	7
Chemical Resistance	C650	Resistant	Resistant

QUALITY WARRANTY



Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).



Recycled Content:
Porcelain: 45.4% Pre-consumer
1.5% Post-consumer
Ceramic: 39.1% Pre-consumer
12.6% Post-consumer



Standard quality tiles manufactured by Eliane Ceramic Tiles meet ISO 13006, ANSI A137.1 standards.



Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.

Porcelain tiles on this series are:



TITAN
PORCELAIN TILES & CERAMIC MOSAICS

