

TULSA

GLAZED PORCELAIN TILES



TULSA

GLAZED PORCELAIN TILES

Tulsa Nero



30x60 cm | 12"x24"
AC (SATIN)

Tulsa Gray



30x60 cm | 12"x24"
AC (SATIN)

Tulsa White



30x60 cm | 12"x24"
AC (SATIN)

Finish
AC (Satin)

Tulsa Hex Nero



20x23 cm | 8"x9"
AC (SATIN)

Tulsa Hex Gray



20x23 cm | 8"x9"
AC (SATIN)

Tulsa Hex White



20x23 cm | 8"x9"
AC (SATIN)



Keystone Nero



TULSA

GLAZED PORCELAIN TILES

SIZES

		Product	Finish	Rect.	Work Size	Thick	Faces	Sq. Ft./ Carton	Pieces/ Carton
	Wall/Floor 12"x 24"	Keystone AC	Satin	No	302.3 x 601.2 mm 11-7/8" x 23-5/8"	7.5 mm	18	17.60	9
	Wall/Floor Hex 8"x 9"	Keystone Hex AC	Satin	No	200.4 x 231.6 mm 7-7/8" x 9-1/8"	8.0 mm	20	9.37	25

USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Exterior Walls Applications	N/A	✓
Interior Walls/Backsplashes	N/A	✓
Interior Countertops	N/A	✓
Facades	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

Note: Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

INSTALLATION AND CARE

Grout Joint Recommendation 1/8"

Shade Variation  V2 - SLIGHT VARIATION

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane's recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Eliane recommends using a cloth with water and a neutral cleaner (soap less) or a general household cleaner.

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	≤ 0.5%
Breaking Strength	C648	≥ 275 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	≥0.42
Surface Abrasion (PEI)	C1027	3 - 4
Frost Resistance	C1026	Yes
Scratch Hardness	MOHS	7 - 8
Chemical Resistance	C650	Resistant



Keystone Gray faces

TULSA

GLAZED PORCELAIN TILES



Keystone White ✓

QUALITY WARRANTY

QUALITY

Standard quality tiles
manufactured by Eliane
Ceramic Tiles meet or exceed
ISO 13006, NBR 15463 and
NBR 13818, ANSI A137.1
standards.



Eliane Porcelain Tiles are certified, ANSI/ASTM compliant, $\leq 0.5\%$ water absorption.

VOC FREE

Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).

(FIRE PROOF)

Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.