

ProLinear

Plus

PRODUCT INFORMATION

Type / Size	Finish	Rectified	Unit	Work Size mm	Thick mm	Faces	SF/ Carton	Pieces/ Carton
 7.5x15 cm 3x6 FLAT	GLOSS / MATTE	NO	SF	76.3 x 154.6	7.00	1	1012	80
 10x20 cm 4x8 FLAT	GLOSS / MATTE	NO	SF	100.0 x 200.0	7.00	1	11.84	55
 10x20 cm 4x8 BEVEL	GLOSS / MATTE	NO	SF	100.0 x 200.0	7.70	1	1076	50
 10x20 cm 4x8 FRAME	GLOSS / MATTE	NO	SF	100.0 x 200.0	7.70	1	1076	50
 10x30 cm 4x12 FLAT	GLOSS / MATTE	NO	SF	100.0 x 300.0	7.00	1	10.98	34
 10x30 cm 4x12 BEVEL	GLOSS / MATTE	NO	SF	100.0 x 300.0	9.00	1	8.40	26
 10x30 cm 4x12 FRAME	GLOSS / MATTE	NO	SF	100.0 x 300.0	9.00	1	8.40	26
 10x40 cm 4x16 FLAT	GLOSS / MATTE	NO	SF	100.0 x 400.0	7.00	1	14.64	34
 TRIM 6" SIDE 7.5x15 cm 3x6 REL*	GLOSS / MATTE	NO	PC	73.7 x 154.6	7.00	1	9.80	80
 TRIM 3" SIDE 7.5x15 cm 3x6 RES**	GLOSS / MATTE	NO	PC	76.3 x 151.8	7.00	1	10.01	80
 TRIM 8" SIDE 10x20 cm 4x8 REL*	GLOSS / MATTE	NO	PC	97.2 x 200.0	7.00	1	11.52	55
 TRIM 4" SIDE 10x20 cm 4x8 RES**	GLOSS / MATTE	NO	PC	100.0 x 197.2	7.00	1	11.63	55
 TRIM 12" SIDE 10x30 cm 4x12 REL*	GLOSS / MATTE	NO	PC	97.2 x 300.0	7.00	1	10.66	34
 TRIM 4" SIDE 10x30 cm 4x12 RES**	GLOSS / MATTE	NO	PC	100.0 x 297.2	7.00	1	10.87	34
 TRIM 16" SIDE 10x40 cm 4x16 REL*	GLOSS / MATTE	NO	PC	97.2 x 400.0	7.00	1	14.21	34
 TRIM 4" SIDE 10x40 cm 4x16 RES**	GLOSS / MATTE	NO	PC	100.0 x 397.2	7.00	1	14.53	34

*REL - Rectified Edge Long
**RES - Rectified Edge Short

USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes - Interior (Residential or Commercial)	N/A	✓
Countertops	N/A	✓
Facades	N/A	
Pool Linings	N/A	

INSTALLATION AND CARE

Grout Joint Recommendation	2 mm - 1/16"
Shade Variation	V1
Professional tile installation is recommended. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.	
We recommend using a cloth with water and a neutral cleaner (soap less) or a general household cleaner for wall tiles cleaning.	

PERFORMANCE CHARACTERISTICS

	NORM	Result
Water Absorption	(ANSI A137.1/ASTM C373-16)	≤ 20%
Breaking Strength	(ANSI A137.1/ASTM C648-04)	≥ 125 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	N/A
Scratch Hardness	MOHS	4
Frost Resistance	(ISO 13006/ ISO 10545)	No
Chemical Resistance	(ANSI A137.1/ASTM 650-04)	A
Stain Resistance	(ANSI A137.1/ASTM C1378-04)	A

QUALITY WARRANTY

QUALITY	Standard quality tiles meet or exceed ISO 13006, ANSI A137.1 standards.	FIRE PROOF	Ceramic tiles are NOT flammable.
VOC FREE	Ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).		