


COLOR MIND

WALL CERAMIC TILES



COLOR MIND WALL CERAMIC TILES

COLOR MIND LIGHT AC | BR



7x25 cm | 3"x10"
AC (SATIN) | BR (GLOSSY)

COLOR MIND BLACK AC | BR



7x25 cm | 3"x10"
AC (SATIN) | BR (GLOSSY)

COLOR MIND ABSINTO BR



7x25 cm | 3"x10"
BR (GLOSSY)

COLOR MIND CEREJA BR



7x25 cm | 3"x10"
BR (GLOSSY)

COLOR MIND VANILLA AC | BR



7x25 cm | 3"x10"
AC (SATIN) | BR (GLOSSY)

COLOR MIND BRUT AC | BR



7x25 cm | 3"x10"
AC (SATIN) | BR (GLOSSY)

COLOR MIND NAVY BR



7x25 cm | 3"x10"
BR (GLOSSY)

COLOR MIND LAZULI BR



7x25 cm | 3"x10"
BR (GLOSSY)

COLOR MIND INOX AC | BR



7x25 cm | 3"x10"
AC (SATIN) | BR (GLOSSY)

COLOR MIND MANGO BR



7x25 cm | 3"x10"
BR (GLOSSY)

COLOR MIND LEMON BR



7x25 cm | 3"x10"
BR (GLOSSY)



WALLS



FIRE PROOF



VOC FREE

COLOR MIND

WALL CERAMIC TILES

PRODUCT INFORMATION

	Type / Size	Series	Finish	Rectified	Unit	Work Size (mm)	Thick	Faces	Sq. Ft./ Carton	Pieces/ Carton
	Wall Tiles 3"x10"	COLOR MIND	Glossy Satin	No	SF	70x250	7mm	1	5.60	30

USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes - Interior	N/A	✓
Countertops	N/A	
Facades	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1- A326.3

QUALITY WARRANTY

 QUALITY	Standard quality tiles manufactured by Eliane Ceramic Tiles meet or exceed ISO 13006, NBR 15463 and NBR 13818, ANSI A137.1 standards
 FIRE PROOF	Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics

 VOC FREE	Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC)
---	--

INSTALLATION AND CARE

Min. Grout Joint Recommendation 1/16"
Shade Variation  V1 - UNIFORM APPEARANCE

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane's recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Eliane recommends using a cloth with water and a neutral cleaner (soap less).

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	≤ 20%
Breaking Strength	C648	≥ 125 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	N/A
Scratch Hardness	MOHS	4
Frost Resistance	C1026	No
Chemical Resistance	C650	Class A - E
Stain Resistance	C1378	Class A



