

# GALAXY SACARA CRISTAL

PORCELAIN & CERAMIC TILES



# GALAXY SACARA CRISTAL

PORCELAIN & CERAMIC TILES

  CERAMIC WALL TILES

## Galaxy Sacara Edro Cristal



32x60 cm | 13"x24" [rectified]  
AC (SATIN)  
18 FACES

   GLAZED PORCELAIN TILES

## Galaxy Sacara Cristal



60x120 cm | 24"x48" [rectified]  
AC (Satin) - DCOFWET  $\geq 0.42$   
PO (Polished) - DCOFWET  $< 0.42$   
18 FACES

## Galaxy Sacara Cristal



60x60 cm | 24"x24" [rectified]  
AC (Satin) - DCOFWET  $\geq 0.42$   
PO (Polished) - DCOFWET  $< 0.42$   
24 FACES

## Galaxy Sacara Cristal



30x60 cm | 12"x24" [rectified]  
AC (Satin) - DCOFWET  $\geq 0.42$   
PO (Polished) - DCOFWET  $< 0.42$   
24 FACES

## Galaxy Sacara Cristal



30x30 cm | 12"x12" sheet  
2"x2" cuts [rectified]  
AC (Satin) - DCOFWET  $\geq 0.42$   
PO (Polished) - DCOFWET  $< 0.42$   
TBI FACES



9.5x60 cm | 4"x24" [rectified]  
AC (Satin) - DCOFWET  $\geq 0.42$   
PO (Polished) - DCOFWET  $< 0.42$



# GALAXY SACARA CRISTAL

## PORCELAIN & CERAMIC TILES

### SIZES AND PACKING

	Finish	Rect.	Work Size	Thick	Faces	Sq. Ft./ Carton	Pieces/ Carton
	13"x24" Deco Wall tile	AC (SATIN)	Yes	320 x 600mm	9.3 mm	TBI	16.47 8
	24"x48" Wall /floor	AC (SATIN)	Yes	600 x 1200 mm	9.5 mm	16-18	15.50 2
		PO (POLISHED)	Yes	600 x 1200 mm	10.5 mm	16-18	15.50 2
	24"x24" Wall /floor	AC (SATIN)	Yes	600 x 600 mm	8.5 mm	24	19.38 5
		PO (POLISHED)	Yes	600 x 600 mm	9.3 mm	24	19.38 5
	12"x24" Wall /floor	AC (SATIN)	Yes	299.5 x 600 mm	8.5 mm	24	13.56 7
		PO (POLISHED)	Yes	299.5 x 600 mm	8.5 mm	24	13/56 7
<b>sheet size</b>							
	2"x2" Mosaic	AC (SATIN)	Yes	299.5 x 299.5 mm	8.5 mm	TBI	9.69 10
		PO (POLISHED)	Yes	299.5 x 299.5 mm	TBI	TBI	9.69 10
	4"x24" Bullnose	AC (SATIN)	Yes	95 x 600 mm	8.5 mm	-	- 12
		PO (POLISHED)	Yes	95 x 600 mm	9.3 mm	-	- 12

### USAGE RECOMMENDATION

	Target DCOF wet	Ceramic Wall Suitable	Porcelain Suitable
Dry & Level – Interior Floor ( Residential / Light Commercial )	N/A		✓
Wet & Level – Interior Floor ( Residential / Light Commercial )	≥ 0.42		✓ AC
Shower Floors ( Residential / Light Commercial )	≥ 0.42		✓ AC
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60		
Ramps & Inclines	≥ 0.65		
Exterior Walls Applications	N/A		✓
Interior Walls/Backsplashes	N/A	✓	✓
Interior Countertops	N/A		✓
Facades	N/A		✓
Pool Linings	N/A		

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

Note: Porcelain tiles are suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

### SUSTAINABILITY



Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).



Recycled Content:  
Porcelain: TBI Pre-consumer  
TBI Post-consumer  
Ceramic: TBI Pre-consumer  
TBI Post-consumer

### INSTALLATION AND CARE

Grout Joint Recommendation 1/16" ( 1 mm )  
Shade Variation V2

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane's recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Eliane recommends using a cloth with water and a neutral cleaner (soap less) or a general household cleaner.

### PERFORMANCE CHARACTERISTICS

	ASTM#	Ceramic Wall Result	Porcelain Result
Water Absorption	C373	≤ 20%	≤ 0.5%
Breaking Strength	C648	≥ 125 lbs	≥ 275 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	N/A	≥ 0.42 AC < 0.42 PO
Frost Resistance	C1026	No	Yes
Scratch Hardness	MOHS	TBI	4-5
Chemical Resistance	C650	Resistant	Resistant
Stain Resistance	C1378	Resistant	Resistant

### QUALITY WARRANTY



Standard quality tiles manufactured by Eliane Ceramic Tiles meet ISO 13006, ANSI A137.1 standards.



Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.




Porcelain Tiles are certified, ANSI/ASTM compliant, ≤ 0.5% water absorption.



GALAXY SACARA CRISTAL 24x24 FACES



GALAXY SACARA CRISTAL 24X48FACES



GALAXY SACARA CRISTAL 12x24 FACES